



Frosted frameless mirror with clip fasteners and 1/4" plate glass with polished edges:

Product Materials

MIRROR: first quality 1/4" float glass and thermosetting infrared-cured paint backing. Manufactured in accordance with ASTM C 1036 and ASTM C 1503. Edges ground and polished smooth.

Design Option Codes

Code	Description
-S	Solid acid-etched border

Installation

Verify all rough-in dimensions prior to installation. Secure mounting clips (metal) to wall with screws included, then engage mirror into clips.

Guide Specification

Frameless mirror shall be of first quality 1/4" float glass, guaranteed for 15 years against silver spoilage. Edges ground and polished smooth.

Frosted Frameless Mirror shall be Bradley Model 747F.



ADA Compliant

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.

Models

Width (Inches)	Height (Inches)	Design Option	Standard Model Number
18"	30"	S	747F-018300S
18"	36"	S	747F-018360S
24"	36"	S	747F-024360S

Mounting Height Guide

Dim. "A":	For Dim. "A"	Bottom of Unit
Mirror's bottom edge of the reflecting surface to finished floor	40" (1016mm)	37" (9406mm)
	37" (940mm)	34" (864mm)
	34" (864mm)	31" (787mm)

