

# Air-Loc® Smoke Testing



## Smoke Blower Features:

- Effectively identifies inflow
- For use with traditional smoke bombs or liquid smoke
- Available with Briggs & Stratton engine
- Generates up to 3,769 cubic feet per minute of air flow<sup>1</sup>
- Made of lightweight, cast aluminum



## Equipped with:

- ½" foam cell gasket to ensure a leak-free seal on manholes and minimize vibration
- Smoke bomb box holder (traditional smoke blower only)
- Pressurized tank, hose and all necessary components (liquid smoke blower only)

## Smoke Fluid Features:

- Produces thick, dense smoke
- Easy-to-regulate
- Virtually indefinite storage life
- Improved packaging for ease in pouring



## Smoke Bomb Features:

- Produces a thick, dense smoke
- Time-proven
- Simple to use
- Can be used with most smoke blowers
- 3 minute bombs available with double wick that allows units to be strung together for a longer smoke time



## Smoke Bomb

Part Number	Description
303550	Smoke Bomb Smoke Blower Kit: Briggs & Stratton engine
034348	Smoke Bomb: 30 seconds (12 per case)
034358	Smoke Bomb: 60-seconds (12 per case)
034368	Smoke Bomb: 3 minutes (12 per case)
034378	Smoke Bomb: 3 minutes, double wick (12 per case)

## Smoke Fluid

Part Number	Description
303008	Smoke Fluid Smoke blower Kit: Briggs & Stratton engine
036488	Fluid Smoke pressure container and hose: 2 gallons capacity
065808	Fluid Smoke: one gallon (1 per case)
065818	Fluid Smoke: five gallons (1 per case)
065828	Fluid Smoke: fifty-five gallon drum

## Accessories

Part Number	Description
014722	Smoke Blower replacement fan (left pitch)
058368	Smoke bomb holding cage
036308	Fluid Smoke conversion kit from Smoke Bomb Briggs & Stratton engine

<sup>1</sup> - CFM performance based on independent laboratory tests. When tested side-by-side at an independent air flow laboratory, Cherne's line stringer, ventilator, and smoke blower beat the competition at every flow condition.

