

Sink Faucet Deckmount

8" Deck- TUF-TECK® compression structures

Model No: 26T3934

COMPLIES WITH:

CSA certified.

- Complies to ASME A112.18.1/ CSA B125.1
- Verified compliant with 0.25% weighted average Pb content regulations
- (Contact Delta Representative for State and/or Local Approvals)





NOTES:

26C3 - 8" Deck- CER-TECK® ceramic structures

SPECIFICATION:


- Heavy Duty Cast Brass sink faucet
- 203 mm (8") centers
- Two handle
- Polished chrome plated finish
- Metal hold-down package
- TUF-TECK® compression structures
- 90% flow with first 1/4 turn of operation
- Positive shutoff even in poor water conditions
- Spout#: 9 Gooseneck spout-6.0" spout reach 10.4" height (unmounted)-Standard rigid/swivel field installation unless LS Limited swing option selected- Vandal resistant .090" wall thickness-(R4)
- Outlet#: 3 Vandal Resistant Aerator Outlet- 1.5 GPM (5.7 L/min) Flow Rate at 60 psi- pressure compensating
- Handle#: 4 102 mm (4") Blade Handles- ADA Compliant-Sanitary Hoods-Metal-Color indexed-Vandal resistant screws

OPERATION:

Not Available

(Dimensional drawing on following page)





Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced April 21, 2021.