Defining Luxury Since 1959

# Single Lever Lavatory Faucet

291-08



## **TECHNICAL DETAILS**

ADA Compliance: No Deck Thickness Maximum: 2"

Deck Thickness Minimum: 1/8"

Fitting Hole Diameter: 1 1/8"

Number of Holes: Three Hole

Number of Handles: Two

Handle Spread Maximum: 12"

Handle Spread Minimum: 8"

nandie Spread Millindin. 6

Handle Turn Angle:

Spout Reach:

Spout Height: 7"

Inlet Connection Type: Male 1/2" NPSM

Installation Type: Deck Mounted

Primary Material: Brass

Valve Material: Ceramic

Flow Restriction: 1.2 gpm

Water Pressure Maximum: 85 PSI Water Pressure Minimum: 20 PSI

Water Pressure Recommended: 60 PSI

#### **PRODUCT FEATURES**

- Style: Contemporary
- Collection: Stria
- Temperature Controlled By Handles
- Cube Handle

### **CODES & STANDARDS**



ASME A112.181/CSA B1251, ASME 112.18.2/CSA B125.2, ANSI NSF, CEC, Watersense 61 Sect. 9, State of MA.

#### WARRANTY

Mechanical Warranty: 10 Years from date of purchase. Finish Warranty: See catalog for further information.



