For Residential and Commercial Applications							
Job Name		Engineer / Architect					
Job Location		Wholesaler					
Submittal Date		Contractor					

## PLB104/115X

## 1/4 Turn Angle Stop – Barbed PEX Inlet

Use: For use only in potable water distribution systems, hot and cold, in accessible locations only

Part Listing:


PLB104X B 1/2" nom crimp barb (for PEX) x 3/8" OD compression, chrome plated, bulk 1/2" nom crimp barb (for PEX) x 3/8" OD compression, chrome plated, bagged PLB104X P 1/2" nom crimp barb (for PEX) x 1/4" OD compression, chrome plated, bagged PLB115X P



STOP MATERIAL SPECIFICATIONS					
Body	Brass, plated				
Stem	Brass				
Ball	Brass, plated				
Seats	PTFE				
O-ring	Rubber				
Handle	ABS, plated				
Handle Screw	Stainless steel				
Compression Nut	Brass, plated				
Compression Sleeve	Brass				
Adaptor	Brass, plated				

Operating Specifications				
Temperature	Pressure			
Intermittent 40°- 160° F	125 PSI maximum			

PART DIMENSIONS (Inches)								
Model	DIM. A	DIM. B	DIM. C	DIM. D	DIM. E	DIM. F		
PLB104X	2.02	1.77	2.23	1.12	1.10	.94		
PLB115X	2.02	1.77	2.23	1.12	1.12	.94		



## С 3/8"OD Comp Ε 1/2"Nom Crimp Barb

## **Listings & Certifications:**

IAPMO listed to ASME A112.18.1 / CSA B125.1 (includes NSF/ANSI 372 and NSF/ANSI/CAN 61)





This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.