



ViegaPEX Ultra tubing
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5003

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¼	100	white	3.200	1	32011	1
¼	500	white	14.000	1	32015	1
¾	100	white	5.000	1	32001¹	1
¾	500	white	21.000	1	32005¹	1
¾	1000	white	42.000	1	32000	1
½	100	white	6.000	1	32021¹	1
½	300	white	17.100	1	32023¹	1
½	500	white	28.000	1	32025¹	1
½	1000	white	55.000	1	32020¹	1
¾	100	white	11.000	1	32041¹	1
¾	300	white	32.100	1	32043¹	1
¾	500	white	53.000	1	32045¹	1
1	100	white	17.000	1	32061¹	1
1	300	white	51.900	1	32063¹	1
1	500	white	88.000	1	32065	1

¹⁾ center pull coil



ViegaPEX Ultra tubing
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5003.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	10	white	0.540	50	33273	1
½	20	white	1.080	50	33020	1
¾	10	white	1.020	25	33276	1
¾	20	white	2.060	25	33045	1
1	20	white	3.420	5	33061	1



ViegaPEX Ultra tubing
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5009

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	100	black	5.500	1	32721	1
½	300	black	16.500	1	32723	1
½	500	black	29.000	1	32725	1



ViegaPEX Ultra tubing
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 UV resistance 6 months
UL listed for NFPA 13D systems, ASTM F876, ASTM F877
Model V5009.1

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¾	100	black	10.500	1	34741	1
¾	300	black	31.500	1	34743	1
¾	500	black	52.500	1	34745	1
1	100	black	17.400	1	34761	1
1	500	black	87.000	1	34765	1
1¼	100	black	25.500	1	34771	1
1¼	300	black	76.500	1	34773	1
1½	100	black	35.400	1	34781	1
2	100	black	63.000	1	32791	1



ViegaPEX Ultra tubing
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 UV resistance 6 months
ASTM F876, ASTM F877
Model V5009.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	20	black	1.100	50	33720	1



ViegaPEX Ultra tubing
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 UV resistance 6 months
UL listed for NFPA 13D systems, ASTM F876, ASTM F877
Model V5009.51

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¾	20	black	2.100	25	35745	1
1	20	black	3.480	5	35761	1
1¼	20	black	5.100	5	35771	1
1½	20	black	7.060	5	35781	1
2	20	black	12.280	5	33791	1



ViegaPEX Ultra tubing
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 UV resistance 6 months
 ASTM F876, ASTM F877
Model V5003

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¼	100	white	3.200	1	32011	1
¼	500	white	14.000	1	32015	1
⅜	100	white	5.000	1	32001¹	1
⅜	500	white	21.000	1	32005¹	1
⅜	1000	white	42.000	1	32000	1
½	100	white	6.000	1	32021¹	1
½	300	white	17.100	1	32023¹	1
½	500	white	28.000	1	32025¹	1
½	1000	white	55.000	1	32020¹	1
¾	100	white	11.000	1	32041¹	1
¾	300	white	32.100	1	32043¹	1
¾	500	white	53.000	1	32045¹	1
1	100	white	17.000	1	32061¹	1
1	300	white	51.900	1	32063¹	1
1	500	white	88.000	1	32065	1

¹⁾ center pull coil



ViegaPEX Ultra tubing
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 UV resistance 6 months
 ASTM F876, ASTM F877
Model V5003.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	10	white	0.540	50	33273	1
½	20	white	1.080	50	33020	1
¾	10	white	1.020	25	33276	1
¾	20	white	2.060	25	33045	1
1	20	white	3.420	5	33061	1



ViegaPEX Ultra tubing
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 UV resistance 6 months
 ASTM F876, ASTM F877
Model V5009

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	100	black	5.500	1	32721	1
½	300	black	16.500	1	32723	1
½	500	black	29.000	1	32725	1



ViegaPEX Ultra tubing
 - PEX
 - Coil
Technical Data
 PEX designation code 5306
 UV resistance 6 months
 UL listed for NFPA 13D systems, ASTM F876,
 ASTM F877
Model V5009.1

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¾	100	black	10.500	1	34741	1
¾	300	black	31.500	1	34743	1
¾	500	black	52.500	1	34745	1
1	100	black	17.400	1	34761	1
1	500	black	87.000	1	34765	1



ViegaPEX Ultra tubing
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 UV resistance 6 months
 ASTM F876, ASTM F877
Model V5009.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	20	black	1.100	50	33720	1



ViegaPEX Ultra tubing
 - PEX
 - Straight length
Technical Data
 PEX designation code 5306
 UV resistance 6 months
 UL listed for NFPA 13D systems, ASTM F876,
 ASTM F877
Model V5009.51

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¾	20	black	2.100	25	35745	1
1	20	black	3.480	5	35761	1